

Typical Application

- Factory
- Body Shop
- Industrial Locations

Options

- ☐ Pressure gauge
- ☐ Speed control switch
- ☐ Different variety of filters to suit application
- ☐ Can be ducted
(may affect fan performance)

The SO2000-I Unit Eliminates Dust, Smoke, Oil Mist, Chemicals and much more

Standard Features

- ✓ Easy installation
- ✓ Simple & inexpensive maintenance
1 minute per month / less than 0.40 per day
- No Cleaning
- No Cracking or Popping
- No Ozone Produced
- No Cleaning Contract Needed



Technical Specifications

Cabinet	16 Gauge Steel
Dimensions	24"(W) x 24"(H) x 48"(L)
CFM Rating	2000
Motor	Torsion Flex with Automatic Shut Off
Blower	Direct Drive Centrifugal
Weight	125 lbs.
Electrical	115 volts, 10 amps, 2 speed toggle switch
Coverage	1 unit per 1500-2000 sq.ft.
Filters	1 – 4" Pleated Pre Filter
	1 – 15" Multi Pocket Filter
	1 – 6" Final Phase H.E.P.A. Filter

Distributed by:

 **Sourcetec**
The future is clean air ... the future is **Sourcetec**®

SOURCECETEC INDUSTRIES INC.

Mississauga, Ontario, Canada

Tel: (905) 678-9333 Fax: (905) 678-7133

Holland, Ohio, USA 1-800-784-2383

www.sourcetecindustries.com

E-mail: sales@sourcetecindustries.com